



VORTEK

TWO JOBS – ONE PASS

Vortek couples with many Vertical Tillage machines

John Deere - Vertical Tillage



Seed Metering Auger



Kuhn Krause Excellerator - Vertical Tillage



Easy Fill Tank Opening with Sealed Lid - 22" x 22"



Great Plains - Vertical Tillage



Farmet - Short Disc



Minimal Hookup Points





**Save Time by Tilling
& Seeding in the Same Pass**



Spacious, Easy Access Platform

2" Distribution Hoses Reduce Plugging



Deflector



Salford - Vertical Tillage

Specifications

MAIN UNIT

Overall Dim.: 102"W x 144" L x 103"H
(without hitch extender)

Empty Weight: 4800 lbs.

Max Gross Weight: 18,000 lbs.

TANK DETAILS

Pressurized Tank for even seed flow

Tank Dim.: 82"L x 102" W x 72"H

Tank Opening: 22"W x 22"L

Tank Capacity: 130 bu.

TIRE SPECS

Flotation Tires: 560/60 R22.5

Wheel Spacing: 80" on center

METERING DETAILS

Meter Type: Hydraulic-driven
Metering Auger

Fan Max RPM: 5,000 RPM

Hydraulic Requirements:
One Circuit – 14 gpm flow

DISTRIBUTION TOWER

Bolt on Kits available for
any tillage implement

Tower Mount Outlets:
8 to 24 outlets available
for tillage equipment up to 60'

HOOKUP POINTS

- 1- 6" Trunk Line
- 2 - Hydraulic Hoses
- 1 - Case Drain
- 1 - Rate Control Cable
- 1 - Flasher Hookup

RATE CONTROL

ISOBUS plugs into your tractor
monitor

Scales - Know your weight
from the tractor



The Vortek Seeding System — *Productivity Made Simple.*

VORTEK
TWO JOBS - ONE PASS
VortekSeeder.com

Vortek
255 Buchanan Road
Honey Brook, PA
610-469-4169

